

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
15 April 2004 (15.04.2004)

PCT

(10) International Publication Number
WO 2004/031530 A1

(51) International Patent Classification⁷: **E21B 4/14**

[IE/IE]; 38 The Hazels, Oakleigh Wood, Ennis, County Clare (IE).

(21) International Application Number:

PCT/IE2003/000132

(74) Agents: **SHORTT, Peter, Bernard et al.**; Tomkins & Co.,
5 Dartmouth Road, Dublin 6 (IE).

(22) International Filing Date:

30 September 2003 (30.09.2003)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

S20020794

4 October 2002 (04.10.2002) IE

(71) Applicant: **MINROC TECHNICAL PROMOTIONS
LIMITED** [IE/IE]; Smithstown, Shannon, County Clare
(IE).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC,
SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA,
UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **PURCELL, Joseph**

[Continued on next page]

(54) Title: A DOWN-THE HOLE HAMMER



(57) Abstract: A down-the-hole hammer is described. It comprises an external cylindrical outer wear sleeve (10), an inner cylinder (9) mounted co-axially within the outer wear sleeve (10), a sliding piston (11) mounted for reciprocating movement within the inner cylinder (9) and the outer wear sleeve (10), to strike a hammer bit (40) mounted at the lower end of the outer wear sleeve (10) and an elongate cylindrical air distributor (3) positioned within the hammer assembly. The lower end of the air distributor (3) is positioned substantially concentrically within the upper end of the inner cylinder (9). A shoulder (38) on the air distributor (3) engages the underside of a complementary shoulder (15) on the inner cylinder (9). The top end of the outer wear sleeve (10) is screw-threadably engaged with the lower end of an annular air distributor mount (2), and the top end of the inner cylinder (9) abuts the lower end of the distributor mount (2) such that the inner cylinder is rigidly mounted in the drill assembly relative to the outer wear sleeve (10).

WO 2004/031530 A1